

phone accessories gate

accessories phone and gate



DoorKing, Inc.
120 Glasgow Avenue
Inglewood, California 90301 U.S.A.

total access control

Telephone: 310-645-0023 1-800-826-7493 FAX: 310-641-1586 E-mail: info@doorking.com www.doorking.com
© 2000 All Rights Reserved. Product specifications may change without notice. Printed in U.S.A. Rev. 12/00

www.doorking.com



total access control



telephone handset
with armored cable is typically used in high noise areas.



surge protectors are available for low voltage; high voltage and telephone line and help protect equipment from transient voltage spikes.



stainless steel housing replaces the black housing on surface mount units and is typically used in coastal areas and for aesthetic looks.



small 12 volt gel cell provides back-up power for telephone entry systems.



fire and postal lock boxes permit emergency vehicle and postal service access.



reversing edge
Electric edge sensors are padded and reverse gates on contact.



plug-in loop detectors simplify installation and are used for vehicle protection.



heavy-duty flange bearing hinges provide excellent support and ease of operation for swing gates of all sizes.



stainless steel trim ring can be used to create a surface mount look with a flush mount unit.



lockable transformer box holds up to four 20 VA accessory transformers and can be used indoors and outdoors. ETL listed.



external speaker is weather proof and designed for use with telephone entry systems installed in high noise areas.



surface mount trim ring is used to recess surface mount units into a wall or pilaster.



endless idler assembly is used with slide gate operators installed in a rear drive configuration.



v-wheels
Steel and UHMW wheels are available in both single and tandem configurations.



3 Button Control
Three-button control station is designed for use in applications where the motorized gate is under manual control.



guide rollers
A variety of guide rollers are available to support slide gates.



fluorescent light kits provide additional external lighting.



stainless steel flush kit includes rough-in box and trim ring. Simplifies installation of flush mount units.



standard and lighted add-on directories for use with standard telephone entry systems.



tracker expansion board control panel houses up to four tracker boards and provides additional convenience outlets.



loop wire with Cross Linked Polyethylene (XLPE) insulation provides superior loop performance and longevity.



photo-beam
Photo-beams provide non-contact protection and will stop or reverse a gate when the beam is broken.



prefabricated ground loops are wired with XLPE insulated wire and are placed in the roadway prior to concrete being poured.



stainless steel chain provides superior strength and inhibits rusting in high humid environments.



elevator board and control panel interfaces with PC programmable systems.



mounting post for telephone entry and access control devices.



transformers
Plug-in, UL listed accessory transformers are available in 12, 16 and 24 volt output.



loop sealant provides a durable, flexible, watertight seal for ground loops installed in concrete or asphalt.



end retainer secures slide gates in the closed position.



key switches provide an alternate method to open motorized vehicular access gates.



master-slave cable provides necessary conductors to interface DKS gate operators in dual-gate applications. Available in 30, 40 and 50 foot lengths