

## **OutBack Specifications**

Model	Frequency Response	Woofer	Tweeter	Sensitivity (dB)	Power (W)	Dimension	Impedance $(\Omega)$	Weight	Sold As
0B-4.1	80Hz-20kHz	4.5" Long Throw	0.5" Polyamide	87	75	8.625"x 6.75"x 5.875" (219 x 171 x 149mm)	8	4 lbs 9 oz	Pairs
0B-5.1	65Hz-20kHz	5.25" Long Throw	0.75" Mylar Titanium	89	100	9.625''x 7.25''x 6.5'' (244 x 184 x 165mm)	8	5 lbs 1 oz	Pairs
OB-6.1	55Hz-20kHz	6.5" Long Throw	1" Mylar Titanium	90	150	11.875"x 8.5"x 7.5" (302 x 216 x 191mm)	8	7 lbs 3 oz	Pairs
OB-Solo	65Hz-20kHz	5.25" Long Throw	Dual 0.75'' Mylar Titanium	89	100	11.875"x 8.5"x 7.5" (302 x 216 x 191mm)	8	7 lbs 3 oz	Each

## **OutBack Features**

These Russound OutBacks are loaded with features you would expect from outdoor speakers at twice the price.

- Low resonance mineral filled composite cabinets that are stain and water resistant, stable with ultraviolet rays and can withstand temperatures from -50° F to 200° F.
- Drivers are a combination of mylar titanium tweeters and injection molded polypropylene cone woofers that can withstand the extremes of temperature, sun, wind and salt.
- High performance tweeter circuits have auto-reset protection built-in for added reliability.

- The marine-grade hardware supplied is highly corrosion resistant. Gold-plated 5-way speaker binding posts combine maximum signal contact and long life.
- Versatile swivel mounting brackets (included) provide for flexible placement and easy installation.
- Available in white or black. Paintable aluminum mesh grille.
- Multipurpose speakers for indoor or outdoor use.

RIRussound.

5 Forbes Road, Newmarket, New Hampshire 03857 USA

603.659.5170

www.russound.com